

Cathodic Protection Cable

Construction:

Annealed stranded bare copper conforming to ASTM B-8.

A high molecular weight polyethylene (HMW / PE) jacket conforming to ASTM D 1248 I, Class A Cat. 4 Grade E5 is extruded over the copper. The polyethylene insulation also contains a metal deactivator to prevent degradation from copper while the cable is in service.

Gauge	Stranding	Insulation Thickness	Nom. OD	Std. Package	Shipping Weight ~LB/1000'
12	7/.0305"	0.110"	0.309"	3000	48
10	7/.0385"	0.110"	0.316"	2500	60
8	7/.0486"	0.110"	0.368"	6000	113
6	7/.0612"	0.110"	0.398"	5000	124
4	7/.0772"	0.110"	0.445"	4500	182
2	7/.0974"	0.110"	0.512"	3500	262
1	19/.0664"	0.125"	0.584"	2500	344
1/0	19/.0745"	0.125"	0.623"	2250	413
2/0	19/.0837"	0.125"	0.669"	2000	508
4/0	19/.1055"	0.125"	0.773"	1500	772

- Direct Burial
- Sunlight Resistant
- Abrasion Resistant

MADE IN THE USA

Rev 04 11-12-2009

Specifications contained herein reflect current data and are subject to change.

Values are nominal and or approximate.

Kalas Manufacturing, Inc.

25 Main St., P.O. Box 328,

Denver, PA 17517

E-MAIL info@kalaswire.com

P 717 336 5575 **F** 717 335 1926