

Pet Containment Wire

Construction:

Solid or stranded copper conductor insulated with linear low density polyethylene to form a durable single or twisted fence wire for pet containment systems. Temperature rating is 75°C to -65°C 30 Volts or 600 Volts.

.035" Wall Pet Containment

Gauge	Stranding	Insulation Thickness	Nom. OD	Std. Package	Shipping Weight ~LB/1000'
16	1/.0508"	0.035"	0.124"	1000	12
14	1/.0641"	0.035"	0.137"	1000	17
14	7/.0242"	0.035"	0.144"	1000	17
14	19/.0140"	0.035"	0.143"	1000	17

.045" Wall Pet Containment

Gauge	Stranding	Insulation Thickness	Nom. OD	Std. Package	Shipping Weight ~LB/1000'
16	1/.0508"	0.045"	0.146"	1000	14
16	7/.0192"	0.045"	0.148"	1000	14
16	19/.0112"	0.045"	0.149"	1000	14
14	1/.0641"	0.045"	0.157"	1000	19
14	19/.0140"	0.045"	0.161"	1000	19

Twisted Pet Containment

Gauge	Stranding	Insulation Thickness	Nom. OD	Std. Package	Shipping Weight ~LB/1000'
14/2	19/.0140"	0.025"	0.240"	500	30
16/2	19/.0112"	0.025"	0.218"	500	22

- Special stranding, colors and packaging are available upon request.
- Direct Burial
- Sunlight Resistant
- Available with UL labeling and print.

MADE IN THE USA

Rev 02 11-12-2009

Specifications contained herein reflect current data and are subject to change.

Values are nominal and or approximate.

Kalas Manufacturing, Inc.

25 Main St., P.O. Box 328,

Denver, PA 17517

E-MAIL info@kalaswire.com

P 717 336 5575 **F** 717 335 1926