

# PRODUCTS AT A GLANCE

# KALAS :Industrial

Products listed are common Kalas products; other products are available upon request. Please contact sales or customer service for your special requests.

## WELDING CABLE

Please contact sales for additional welding cable constructions and sizes.

**TOUGHFLEX™  
EPDM WELDING CABLE**  
EPDM Rubber  
-50°C to 105°C  
600 Volts  
#6 - 250 MCM

**METRIC  
WELDING CABLE**  
EPDM Rubber  
-50°C to 105°C  
600 Volts  
16mm2 - 120mm2

**FLEXWHIP™**  
EPDM Rubber  
-50°C to 105°C  
600 Volts  
#2 - 4/0

**UL K-90  
WELDING CABLE**  
PVC / Nitrile Rubber  
-35°C to 90°C  
90 Volts  
#6 - 4/0

**K-FLEX™  
TPE WELDING CABLE**  
TPE  
-40°C to 90°C  
600 Volts  
#6 - 500 MCM

## FLEX CORD

**HARD SERVICE CORD PVC**  
SJT, SJTO, SJTOO, SJTW,  
SJTOW, SJTOOW  
PVC Jacket PVC Inners  
-40°C to 60°C or 105°C  
300 Volts  
#18 - #10, 2-4 conductors  
Also available with greater  
than 4 conductors

**HARD SERVICE CORD**  
SJE, SJE0, SJE00, SJEW,  
SJEOW, SJE0OW  
TPE Jacket PVC or TPE Inners  
105°C to -40°C or -50°C  
300 Volts  
#18 - #10, 2-4 conductors  
Also available with greater  
than 4 conductors

**EXTRA HARD SERVICE CORD PVC**  
ST, STO, STOO, STW, STOW,  
STOOW  
PVC Jacket PVC Inners  
-40°C to 60°C or 105°C  
600 Volts  
#18 - #4, 2-4 conductors  
Also available with greater  
than 4 conductors

**EXTRA HARD SERVICE CORD**  
SE, SE0, SE00, SEW, SEOW,  
SE0OW  
TPE Jacket PVC Inners  
105°C to -40°C or -50°C  
600 Volts  
#18 - #4, 2-4 conductors  
Also available with greater  
than 4 conductors  
Stocked in 250' lengths on the  
following constructions 6/3,  
6/4, 8/3, 8/4, 10/3, 10/4

## BATTERY CABLE

**SGT BATTERY CABLE**  
SAE J1127  
PVC -40°C to 80°C  
60 Volts DC  
#6 - 4/0

**140° SGR BATTERY CABLE**  
EPDM  
-60°C to 140°C  
60 Volts DC  
#6 - 4/0  
SAE J1127

**SGR BATTERY CABLE**  
EPDM  
-40°C to 105°C  
60 Volts DC  
#6 - 250 MCM  
SAE J1127  
UL 558, 583

## INDUSTRIAL POWER

**TOUGHFLEX™ TYPE SC  
ENTERTAINMENT CABLE**  
CPE  
-50°C to 105°C  
600 Volts  
#8 - 4/0  
NEC 520, 525, 530  
UL 1680, CSA PPC 22.2 - 96

**PORTABLE POWER CABLE PPC/PPE**  
TPE  
-40°C to 90°C Dry; 75°C Wet  
2000 Volts  
#8 - 300 MCM  
UL MSHA

## MACHINE TOOL WIRE (MTW), COIL LEAD, TEW & TR

**MTW**  
PVC 90°C  
600 Volts  
#18 - 500 MCM

**COIL LEAD  
WIRE CL1251**  
XLPE 125°C  
600 Volts  
#18 - 4/0

**TEW**  
PVC 105°C  
600 Volts  
#18 - 500 MCM

**TR32**  
PVC 90°C  
1400 Volts  
#18 - #10

**TR64**  
PVC 90°C  
600 Volts  
#18 - #14

## CONTRACTOR CORDS

**8/3**  
SJTW  
PVC -40°C to 90°C  
250 Volts DC  
#30 Stranding  
25' & 50' Lengths  
Lighted End  
NEMA 6-50 Plug Type

**10/3**  
SJTW  
PVC -37°C to 91°C  
125 Volts DC  
#30 Stranding  
25', 50', 100' Lengths  
Lighted End  
NEMA 5-15R Plug Type

**12/3**  
SJTW  
PVC -37°C to 91°C  
125 Volts DC  
#30 Stranding  
25', 50', 100' Lengths  
Lighted End  
NEMA 5-15P Plug Type

**12/3 TRIPLE TAP**  
SJTW  
PVC -37°C to 91°C  
125 Volts DC  
#30 Stranding  
25', 50', 100' Lengths  
Lighted End  
NEMA 5-15P Plug Type

**12/3 EXTREME**  
SJTW  
PVC -70°C to 105°C  
125 Volts DC  
#30 Stranding  
25', 50', 100' Lengths  
Lighted End  
NEMA 5-15P Plug Type

**14/3 TROUBLE LIGHT**  
SJTW  
PVC -37°C to 91°C  
125 Volts DC  
#30 Stranding  
25' & 50' Lengths  
NEMA 5-15 Plug Type

**KALAS HEADQUARTERS**  
167 Greenfield Road  
Lancaster, PA 17601

**KALAS LOS ANGELES**  
28365 Constellation Road,  
Unit B  
Valencia, CA 91355

**KALASWIRE.COM/INDUSTRIAL**  
P 717-335-0135  
F 717-335-0846

Specifications contained herein reflect  
current data and are subject to change.

