10/3 Contractor Power Cord





CORD SPECIFICATIONS:

GAUGE	TYPE	STRANDING	VOLTS	AMPS	WATTS	END
10/3	SJTW	#30	125	15	1875	Lighted

PACKAGING:

LENGTH	вох оту	WEIGHT/ UNIT	COLOR
25'	2	6 lbs	Yellow
50'	2	13 lbs	Yellow
100'	2	24 lbs	Yellow

- Highly Flexible
 Jacket remains flexible in cold temperatures with no cracking or breaking
- Operating Temperatures
 Range from +195°F (+91°C) to
 -35°F (-37°C)
- Water Resistant
 Durable construction
 prevents moisture failure
- Lighted End
 Signals cord is powered to
 ensure safety
- Durable Construction
 Resists abrasion, grease, oil, and water. Molded connectors will not break!
- Quality Assured
 Each cord is tested for polarity and approved for indoor and outdoor use
- · Lifetime Warranty
- NEMA 5-15R Plug Type

167 Greenfield Road Lancaster, PA 17601

KALASWIRE.COM/INDUSTRIAL

P 717-335-0135

LAS VEGAS WAREHOUSE

4320 North Lamb Blvd. Suite 300, Las Vegas, Nevada 89115

TULSA WAREHOUSE

1810 East Jasper St. Tulsa, Oklahoma 74110 NOTE: Do not use for 600 volt in-line applications. Product for welding applications only. Specifications contained herein reflect current data and are subject to change. Values are nominal and/or approximate.

MADE IN USA

ISO 9001: 2015 CERTIFIED ISO 14001: 2015 CERTIFIED

