# 12/3 Heavy Duty Power Cord









# **CORD SPECIFICATIONS:**

GAUGE	ТҮРЕ	STRANDING	VOLTS	AMPS	WATTS	ENDS
12/3	SJTW	#30	125	15	1875	Lighted

## **PACKAGING:**

LENGTH	вох стү	WEIGHT/ UNIT	COLOR
25'	12	3.8 lbs	Blue, Red, Yellow
50'	4	7.75 lbs	Blue, Red, Yellow
100'	2	15.5 lbs	Blue, Red, Yellow

# • Heavy Duty Power Cord

Highly flexible annealed 30 gauge bare copper; appropriate for use in all weather applications

## · Highly Flexible

Jacket remains flexible in cold temperatures with no cracking or breaking

## • Operating Temperatures

Range from +195°F (+91°C) to -35°F (-37°C)

#### Water Resistant

Durable construction prevents moisture failure

#### Lighted End

Signals cord is powered to ensure safety

## • Durable Construction

Resists abrasion, grease, oil, and water. Molded connectors will not break!

## Quality Assured

Each cord is tested for polarity and approved for indoor and outdoor use

- · Lifetime Warranty
- NEMA 5-15 Plug Type

167 Greenfield Road Lancaster, PA 17601

## KALASWIRE.COM/INDUSTRIAL

P 717-335-0135

#### LAS VEGAS WAREHOUSE

4320 North Lamb Blvd. Suite 300, Las Vegas, Nevada 89115

#### **TULSA WAREHOUSE**

1810 East Jasper St. Tulsa, Oklahoma 74110 NOTE: Do not use for 600 volt in-line applications. Product for welding applications only. Specifications contained herein reflect current data and are subject to change. Values are nominal and/or approximate.

## MADE IN USA

ISO 9001: 2015 CERTIFIED ISO 14001: 2015 CERTIFIED

