12/3 Extreme Power Cord





CORD SPECIFICATIONS:

GAUGE	ТҮРЕ	STRANDING	VOLTS	AMPS	WATTS	ENDS
12/3	SJEOW	#30	125	15	1875	Lighted

PACKAGING:

LENGTH	BOX QTY WEIGHT/ UNIT		COLOR	
25'	12	12 3.25 lbs		
50'	4	6.5 lbs	Blue	
100'	2	13.0 lbs	Blue	

• Extreme Temperature Power Cord

Remains flexible and performs from +221°F (+105°C) to -94°F (-70° C)

• Heavy Duty Construction

Highly flexible annealed 30 gauge bare copper; appropriate for use in all weather applications

· Highly Flexible

TPE Jacket remains flexible in extreme temperatures

Water Resistant

Durable construction prevents moisture failure

Lighted End

Signals cord is powered to ensure safety

• Durable Construction

Resists abrasion, grease, oil, and water. Molded connectors will not break!

· Quality Assured

Each cord is tested for polarity and approved for indoor and outdoor use

- · Lifetime Warranty
- NEMA 5-15P Plug Type

KALAS MAILING ADDRESS

167 Greenfield Road Lancaster, PA 17601 KALASWIRE.COM/INDUSTRIAL

P 717-335-0135

LAS VEGAS WAREHOUSE

4320 North Lamb Blvd. Suite 300, Las Vegas, Nevada 89115

TULSA WAREHOUSE

1810 East Jasper St. Tulsa, Oklahoma 74110 NOTE: Do not use for 600 volt in-line applications. Product for welding applications only. Specifications contained herein reflect current data and are subject to change. Values are nominal and/or approximate.

MADE IN USA

ISO 9001: 2015 CERTIFIED ISO 14001: 2015 CERTIFIED

