8/3 Heavy Duty Power Cord





CORD SPECIFICATIONS:

GAUGE	ТҮРЕ	LENGTH	VOLTS	AMPS	COLOR
8/3	STW	50'	250	40	Black

PACKAGING:

GAUGE	LENGTH	вох стү	WEIGHT/ UNIT
8/3	25'	4	12 lbs
8/3	50'	2	24 lbs

Right Angle Design

Appropriate for use with applications using 40 amps or less

· Heavy Duty Power Cord

Highly flexible annealed 30 gauge bare copper; appropriate for use in all weather applications

Highly Flexible

Jacket remains flexible in cold temperatures with no cracking or breaking

Operating Temperatures

Range from +194°F (+90°C) to -40°F (40°C)

Water Resistant

Durable construction prevents moisture failure

Lighted End

Signals cord is powered to ensure safety

• Durable Construction

Resists abrasion, grease, oil, and water. Molded connectors will not break!

Quality Assured

Each cord is tested for polarity and approved for indoor and outdoor use

- Lifetime Warranty
- NEMA 6-50 Plug Type

KALAS MAILING ADDRESS

167 Greenfield Road Lancaster, PA 17601 KALASWIRE.COM/INDUSTRIAL

P 717-335-0135

LAS VEGAS WAREHOUSE

4320 North Lamb Blvd. Suite 300,

Las Vegas, Nevada 89115

TULSA WAREHOUSE

1810 East Jasper St. Tulsa, Oklahoma 74110 NOTE: Do not use for 600 volt in-line applications. Product for welding applications only. Specifications contained herein reflect current data and are subject to change. Values are nominal and/or approximate.

MADE IN USA

ISO 9001: 2015 CERTIFIED ISO 14001: 2015 CERTIFIED



RoHS: Kalas products are compliant with the requirements of the RoHS directive (2011/65/EU as amended).