

UTILIFlex™

GROUNDING CABLE

DESIGNED FOR TEMPORARY GROUNDING FOR DE-ENERGIZED OVERHEAD ELECTRICAL LINES AND DE-ENERGIZED ELECTRICAL EQUIPMENT.

CLEAR GROUNDING CABLE

- Highly flexible stranded No. 30 bare copper conductor
- Clear high grade 105°C PVC insulation ensures ability to see stranding and identify breaks
- Meets temperature range and flame retardancy of ASTM F-855, Type III
- Heavier jacket walls provide extra protection from the environment:
 - Superior operating temperature range of -40°C exceeding ASTM F-855 and up to 105°C exceeding ASTM F-855 Type III
 - PermaPrint™, indent print that lasts a life time will not wear off
- Special packaging and custom inkjet print available



TPE GROUNDING CABLE

- Highly flexible stranded No. 30 bare copper conductor
- High grade 105°C TPE insulation
- Meets temperature range of ASTM F-855, Type III
- Excellent operating temperature range of -40°C to 105°C
- Superior flexibility in cold weather
- Special packaging and custom print available
- Yellow and black jacket colors available



KALAS MAILING ADDRESS

167 Greenfield Road
Lancaster, PA 17601

TULSA WAREHOUSE

1810 East Jasper St.
Tulsa, Oklahoma 74110

KALASWIRE.COM

P 717-336-5575

MADE IN THE USA

ISO 9001:2015 CERTIFIED
ISO 14001:2015 CERTIFIED