

Products at a Glance



Products listed are common Kalas products; other products are available upon request. Please contact sales or customer service for your special requests.

Welding Cable

TOUGHFLEX™ EPDM WELDING CABLE

EPDM Rubber
-50°C to 105°C
600 Volts
#6 - 250 MCM

FLEXWHIP™

EPDM Rubber
-50°C to 105°C
600 Volts
#2 - 2/0

Battery Cable

SGT BATTERY CABLE

SAE J1127
PVC -40°C to 80°C
60 Volts DC
#6 - 4/0

SGR BATTERY CABLE

EPDM
-40°C to 105°C
60 Volts DC
#6 - 250 MCM
SAE J1127
UL 558, 583

Flex Cord

SOOW POWER CORD

EPDM Jacket with EPDM Inners
-40C to 90C
600 Volts

Stocked in 250' lengths on the following constructions: 10/3, 10/4, 8/3, 8/4, 6/3, 6/4

Industrial Power

TOUGHFLEX™ TYPE SC ENTERTAINMENT CABLE

CPE
-50°C to 105°C
600 Volts
#8 - 4/0
NEC 520, 525, 530
UL 1680, CSA PPC 22.2 - 96

TOUGHFLEX™ TYPE W PORTABLE POWER CABLE

Dual insulated
EPDM Inner Insulated with CPE Jacket
-40°C to 90°C; 90°C Wet
2000 Volts
#8 - 4/0
NEC 400, NFPA 70
UL 1650, CSA PPC 22.2 - 96
MSHA Flame Test
Sun Res

PORTABLE POWER CABLE PPC/PPE

TPE
-40°C to 90°C Dry; 75°C Wet
2000 Volts
#8 - 300 MCM
UL MSHA

Contractor Cords

8/3

SJTW
PVC -40°C to 90°C
250 Volts DC
#30 Stranding
25', 50', 100' Lengths
Lighted End
NEMA 6-50 Plug Type

10/3

SJTW
PVC -37°C to 91°C
125 Volts DC
#30 Stranding
25', 50', 100' Lengths
Lighted End
NEMA 5-15R Plug Type

12/3

SJTW
PVC -37°C to 91°C
125 Volts DC
#30 Stranding
25', 50', 100' Lengths
Lighted End
NEMA 5-15P Plug Type

12/3 TRIPLE TAP

SJTW
PVC -37°C to 91°C
125 Volts DC
#30 Stranding
25', 50', 100' Lengths
Lighted End
NEMA 5-15P Plug Type

12/3 EXTREME

SJTW
PVC -70°C to 105°C
125 Volts DC
#30 Stranding
25', 50', 100' Lengths
Lighted End
NEMA 5-15P Plug Type

14/3 TROUBLE LIGHT

SJTW
PVC -37°C to 91°C
125 Volts DC
#30 Stranding
25' & 50' Lengths
NEMA 5-15 Plug Type

KALAS MAILING ADDRESS

167 Greenfield Road
Lancaster, PA 17601

TULSA WAREHOUSE

1810 East Jasper St.
Tulsa, Oklahoma 74110

KALASWIRE.COM/INDUSTRIAL

P 717-335-0135

RoHS: Kalas products are compliant with the requirements of the RoHS directive (2011/65/EU as amended).

NOTE: Do not use for 600 volt in-line applications. Product for welding applications only. Specifications contained herein reflect current data and are subject to change. Values are nominal and/or approximate.

MADE IN USA

ISO 9001: 2015 CERTIFIED
ISO 14001: 2015 CERTIFIED



LISTED

Specifications contained herein reflect current data and are subject to change.