

Products at a Glance



Products listed are common Kalas products; other products are available upon request. Please contact sales or customer service for your special requests.

Welding Cable

Please contact sales for additional welding cable constructions and sizes.

TOUGHFLEX™ EPDM WELDING CABLE
EPDM Rubber
-50°C to 105°C
600 Volts
#6 - 250 MCM

METRIC WELDING CABLE
EPDM Rubber
-50°C to 105°C
600 Volts
16mm2 - 120mm2

FLEXWHIP™
EPDM Rubber
-50°C to 105°C
600 Volts
#2 - 2/0

UL K-90 WELDING CABLE
PVC / Nitrile Rubber
-35°C to 90°C
90 Volts
#6 - 4/0

K-FLEX™ TPE WELDING CABLE
TPE
-40°C to 90°C
600 Volts
#6 - 500 MCM

Flex Cord

HARD SERVICE CORD PVC
SJT, SJTO, SJTOO, SJTW, SJTOW, SJTOOW
PVC Jacket PVC Inners
-40°C to 60°C or 105°C
300 Volts
#18 - #10, 2-4 conductors
Also available with greater than 4 conductors

HARD SERVICE CORD
SJE, SJE0, SJE00, SJEW, SJEOW, SJE00W
TPE Jacket PVC or TPE Inners
105°C to -40°C or -50°C
300 Volts
#18 - #10, 2-4 conductors
Also available with greater than 4 conductors

EXTRA HARD SERVICE CORD PVC
ST, STO, STOO, STW, STOW, STOOW
PVC Jacket PVC Inners
-40°C to 60°C or 105°C
600 Volts
#18 - #4, 2-4 conductors
Also available with greater than 4 conductors

EXTRA HARD SERVICE CORD
SE, SE0, SE00, SEW, SEOW, SE00W
TPE Jacket PVC Inners
105°C to -40°C or -50°C
600 Volts
#18 - #4, 2-4 conductors
Also available with greater than 4 conductors
Stocked in 250' lengths on the following constructions 6/3, 6/4, 8/3, 8/4, 10/3, 10/4

Battery Cable

SGT BATTERY CABLE
SAE J1127
PVC -40°C to 80°C
60 Volts DC
#6 - 4/0

140° SGR BATTERY CABLE
EPDM
-60°C to 140°C
60 Volts DC
#6 - 4/0
SAE J1127

SGR BATTERY CABLE
EPDM
-40°C to 105°C
60 Volts DC
#6 - 250 MCM
SAE J1127
UL 558, 583

Industrial Power

TOUGHFLEX™ TYPE SC ENTERTAINMENT CABLE
CPE
-50°C to 105°C
600 Volts
#8 - 4/0
NEC 520, 525, 530
UL 1680, CSA PPC 22.2 - 96

PORTABLE POWER CABLE PPC/PPE
TPE
-40°C to 90°C Dry; 75°C Wet
2000 Volts
#8 - 300 MCM
UL MSHA

TOUGHFLEX™ TYPE W PORTABLE POWER CABLE
Dual insulated
EPDM Inner Insulated with CPE Jacket
-40°C to 90°C; 90°C Wet
2000 Volts
#8 - 4/0
NEC 400, NFPA 70
UL 1650, CSA PPC 22.2 - 96
MSHA Flame Test
Sun Res

Machine Tool Wire (MTW), Coil Lead, TEW & TR

MTW
PVC 90°C
600 Volts
#18 - 500 MCM

COIL LEAD WIRE CL1251
XLPE 125°C
600 Volts
#18 - 4/0

TEW
PVC 105°C
600 Volts
#18 - 500 MCM

TR32
PVC 90°C
1400 Volts
#18 - #10

TR64
PVC 90°C
600 Volts
#18 - #14

Contractor Cords

8/3
SJTW
PVC -40°C to 90°C
250 Volts DC
#30 Stranding
25' & 50' Lengths
Lighted End
NEMA 6-50 Plug Type

10/3
SJTW
PVC -37°C to 91°C
125 Volts DC
#30 Stranding
25', 50', 100' Lengths
Lighted End
NEMA 5-15R Plug Type

12/3
SJTW
PVC -37°C to 91°C
125 Volts DC
#30 Stranding
25', 50', 100' Lengths
Lighted End
NEMA 5-15P Plug Type

12/3 TRIPLE TAP
SJTW
PVC -37°C to 91°C
125 Volts DC
#30 Stranding
25', 50', 100' Lengths
Lighted End
NEMA 5-15P Plug Type

12/3 EXTREME
SJTW
PVC -70°C to 105°C
125 Volts DC
#30 Stranding
25', 50', 100' Lengths
Lighted End
NEMA 5-15P Plug Type

14/3 TROUBLE LIGHT
SJTW
PVC -37°C to 91°C
125 Volts DC
#30 Stranding
25' & 50' Lengths
NEMA 5-15 Plug Type

KALAS MAILING ADDRESS
167 Greenfield Road
Lancaster, PA 17601

KALASWIRE.COM/INDUSTRIAL
P 717-335-0135

LAS VEGAS WAREHOUSE
4320 North Lamb Blvd.
Suite 300,
Las Vegas, Nevada 89115

TULSA WAREHOUSE
1810 East Jasper St.
Tulsa, Oklahoma 74110

NOTE: Do not use for 600 volt in-line applications. Product for welding applications only. Specifications contained herein reflect current data and are subject to change. Values are nominal and/or approximate.

MADE IN USA

ISO 9001: 2015 CERTIFIED
ISO 14001: 2015 CERTIFIED

