


# 12 GAUGE / 14 CONDUCTOR ENTERTAINMENT LIGHTING CABLE



## FEATURES:

- Configuration of singles match orientation of industry 19-pin connectors for simple assembly
- Easy-to-read print on each single conductor for clear identification
- Specially formulated rubber-like jacket designed to withstand repetitive coiling
- Paper separator allows for ease of stripping
- Operating temperatures from -40°C to 105°C
- Flame retardant to UL VW-1

## SPECIFICATIONS:



### PRINT LEGEND SINGLES:

- Numbered (1) through (14)
- Outer: 1, 2, 3, 4, 5, 6, 7, 8, 9, 10
- Inner Core: 11, 12, 13, 14
- Singles identified with easy-to-read alternatively inversed numbering as shown: 4 - FOUR RUF - 4

### CONDUCTOR;

- 12 gauge
- 65 strands
- .010" bare copper

### INSULATION SINGLES;

- PVC compound; 105°C
- .144"+/-.003" OD
- .026" nominal wall
- Grey insulation

### INSULATION JACKET;

- PVC compound; 105°C
- .795"+/-.015" OD
- .080" nominal wall
- Matte black jacket

- Rated to 600 Volts
- Packaging  
1,000' on 36"x16" reel
- Product Weight  
490lb/1,000'
- Paper Separator
- AWM UL Style 2586 Approved
- UL 758 and CSA 22.2 210-05
- ASTM B-3 Copper Conductors
- RoHS and REACH Compliant

### KALAS MAILING ADDRESS

167 Greenfield Road  
Lancaster, PA 17601

### KALASWIRE.COM

P 717-336-5575

### LAS VEGAS WAREHOUSE

4320 North Lamb Blvd.  
Suite 300,  
Las Vegas, Nevada 89115

### TULSA WAREHOUSE

1810 East Jasper St.  
Tulsa, Oklahoma 74110

Call 888 870-1997 for additional cable specifications.

Specifications contained herein reflect current data and are subject to change. Values are nominal and/or approximate.



**RoHS:** Kalas products are compliant with the requirements of the RoHS directive (2011/65/EU as amended).

MADE IN USA