

16 GAUGE / 7 CONDUCTOR SEOW ENTERTAINMENT LIGHTING CABLE



FEATURES:

- TPE jacket designed to withstand repetitive coiling
- Paper separator allows for ease of stripping
- Operating temperatures from -50°C to 105°C
- Flame retardant to UL VW-1

SPECIFICATIONS:

PRINT LEGEND:

- 7/C 16 AWG (1.31mm²) E31793 (UL) SEOW 600V 105°C (WATER RESISTANT 60°C) VW-1 --- 7/C 1.31mm² (16 AWG) LL22035 CSA SEOW 600V 105°C VW-1

CONDUCTOR;

- 16 gauge
- 26 strands
- .010" bare copper

INSULATION SINGLES;

- TPE compound; 105°C
- .123" +/- .003" diameter
- .030" Min. Avg. Wall
- Color/Sequence: Green/Brown/
Light Blue/Yellow/Black/White
with 1 Purple Stripe/Red

JACKET;

- TPE compound; 105°C
- .563" +/- .010" diameter
- .080" Min. Avg. Wall
- Matte black jacket

- Rated to 600 Volts

• Packaging

- 500' on 24"x9"x8" reel
- 1500 ft. on 30"x16"x12" reel

• Product Weight

- 198lb/1,000'

• Paper Separator

• Filler

- UL 62 and CSA 22.2 NO. 49-14

KALAS MAILING ADDRESS

167 Greenfield Road
Lancaster, PA 17601

TULSA WAREHOUSE

1810 East Jasper St.
Tulsa, Oklahoma 74110

KALASWIRE.COM

P 717-336-5575

Call 888 870-1997 for additional cable specifications.
Specifications contained herein reflect current data and are
subject to change. Values are nominal and/or approximate.

MADE IN USA