

GENFLEX™ TYPE SC ENTERTAINMENT CABLE



FEATURES

- Highly flexible cable for optimal ease of movement around objects and coiling cable for transport & storage.
- Resists oil, solvents, ozone, crushing and abrasion.
- Custom print legend available upon request.
- Customizable PermaPrint™ indent print that lasts a lifetime and inkjet print are available on all sizes.
- Available in black or green.
- Meets UL Subject 1680, CSA PPC 22.2 - 96.

APPLICATIONS

- Temporary power uses in applications such as TV, theaters (indoor and outdoor), sound systems, stages, etc.
- National Electrical Code articles 520, 525 and 530.
- Portable lighting systems used for the above applications.

CONSTRUCTION

8 AWG - 250MCM cables available, made with flexible stranded No. 30 bare copper conductor insulated with a high grade CPE. A paper separator is utilized to enhance stripability. Maximum conductor operating temperature is 105°C (221°F) in circuits not exceeding 600 Volts. Minimum temperature rating is -50°C (-58°F).

GENFLEX™ TYPE SC ENTERTAINMENT CABLE



GAUGE	STRANDING	INSULATION THICKNESS		NOMINAL O.D.		STANDARD PACKAGE	SHIPPING WEIGHT -LBS/ 1000 FT.
		in	mm	in	mm		
8	7x24/.0100"	0.110	2.79	0.380	9.65	500	112
6	7x37/.010"	0.110	2.79	0.420	10.67	500	149
4	7x60/.010"	0.110	2.79	0.480	12.19	500	212
2	7x95/.010"	0.110	2.79	0.540	13.72	500	299
1	19x44/.010"	0.110	2.79	0.580	14.73	500	369
1/0	19x56/.010"	0.110	2.79	0.630	16.00	500	458
2/0	19x70/.010"	0.110	2.79	0.680	17.27	500	558
3/0	19x88/.010"	0.110	2.79	0.730	18.54	500	676
4/0	19x111/.010"	0.110	2.79	0.790	20.07	500	826
250 MCM	19x133/.010"	0.110	2.79	0.850	21.59	500	846

KALAS MAILING ADDRESS
167 Greenfield Road
Lancaster, PA 17601

TULSA WAREHOUSE
1810 East Jasper St.
Tulsa, Oklahoma 74110

KALASWIRE.COM
P 717-336-5575