

GENFLEX™ TYPE SC ENTERTAINMENT CABLE



FEATURES

- Highly flexible cable for optimal ease of movement around objects and coiling cable for transport & storage.
- Resists oil, solvents, ozone, crushing and abrasion.
- Custom print legend available upon request.
- Customizable PermaPrint™ indent print that lasts a lifetime and inkjet print are available on all sizes.
- Available in black.
- Meets UL Subject 1680, CSA PPC 22.2 - 96.

APPLICATIONS

- Temporary power uses in applications such as TV, theaters (indoor and outdoor), sound systems, stages, etc.
- National Electrical Code articles 520, 525 and 530.
- Portable lighting systems used for the above applications.

CONSTRUCTION

8 AWG - 250MCM cables available, made with flexible stranded No. 30 bare copper conductor insulated with a high grade RoHS compliant CPE. A paper separator is utilized to enhance stripability. Maximum conductor operating temperature is 105°C (221°F) in circuits not exceeding 600 Volts. Minimum temperature rating is -50°C (-58°F).

GENFLEX™ TYPE SC ENTERTAINMENT CABLE



GAUGE	STRANDING	INSULATION THICKNESS		NOMINAL O.D.		STANDARD PACKAGE	SHIPPING WEIGHT -LBS/ 1000 FT.
		in	mm	in	mm		
8	7x24/.0100"	0.110	2.79	0.380	9.65	500	112
6	7x37/.010"	0.110	2.79	0.420	10.67	500	149
4	7x60/.010"	0.110	2.79	0.480	12.19	500	212
2	7x95/.010"	0.110	2.79	0.540	13.72	500	299
1	19x44/.010"	0.110	2.79	0.580	14.73	500	369
1/0	19x56/.010"	0.110	2.79	0.630	16.00	500	458
2/0	19x70/.010"	0.110	2.79	0.680	17.27	500	558
3/0	19x88/.010"	0.110	2.79	0.730	18.54	500	676
4/0	19x111/.010"	0.110	2.79	0.790	20.07	500	826
250 MCM	19x133/.010"	0.110	2.79	0.850	21.59	500	846

Please contact your Kalas representative to discuss ampacity and voltage drop values based on NEC standards.

KALAS MAILING ADDRESS
167 Greenfield Road
Lancaster, PA 17601

KALASWIRE.COM
P 717-336-5575

LAS VEGAS WAREHOUSE
4320 North Lamb Blvd.
Suite 300,
Las Vegas, Nevada 89115

TULSA WAREHOUSE
1810 East Jasper St.
Tulsa, Oklahoma 74110