

SGR BATTERY CABLE SAE J1127



FEATURES

- Custom print, special stranding and packaging- are available upon request.
- Resistant to acid, abrasion, alkalis, coolant, diesel fuel, ethanol, flame, gas, ozone, power steering fluid, oil and transmission fluid.
- Meets the Battery Cable requirements of UL 558 paragraph 8.1 item (f) and UL 583 paragraph 12.1 item (f).
- UL Approved product, upon request.
- Meets SAE J1127 for SGR.

APPLICATIONS

- For use between battery terminal & starter and grounding, on boats, buses, cars, lift trucks, RV's, tractors and trucks.

CONSTRUCTION

SAE SGR Battery Cable 60V DC is constructed with flexible stranded copper conductor. Insulation is a high grade RoHS compliant -40°C to 105°C EPDM. Kalas SGR Battery Cable is constructed to meet the requirements of SAE J1127.

SGR BATTERY CABLE SAE J1127



GAUGE	STANDARD PART NUMBER	STRANDING	INSULATION THICKNESS		NOMINAL O.D.		STANDARD PACKAGE	SHIPPING WEIGHT -LBS/ 1000 FT.
			in	mm	in	mm		
6	None	37/.0260	0.060	1.52	0.305	7.75	1000	104
6	310198.xxx	7/19/.0137	0.060	1.52	0.310	7.87	1000	107
4	310204.xxx	7/19/.0170	0.065	1.65	0.375	9.53	1000	153
4	300051.xxx	61/.0250	0.065	1.65	0.350	8.89	1000	160
2	300245.00x	7/19/.0218	0.065	1.65	0.438	11.13	1000	248
1	None	7/19/.0243	0.065	1.65	0.480	12.19	1000	308
1/0	300045.xxx	19/7/.0275	0.065	1.65	0.525	13.34	500	383
2/0	310706.xxx	19/7/.0309	0.065	1.65	0.575	14.61	500	470
3/0	310199.xxx	19/84/.010	0.078	1.98	0.641	16.28	500	631
4/0	None	19/109/.010	0.078	1.98	0.711	18.06	500	766
250 MCM *	None	19/133/.010	0.090	2.29	0.795	20.19	500	944

* Manufactured to SAE interpolated data