



FEATURES

- Non-wicking polypropylene and reinforced paper fillers available.
- Made per UL Standard 62 for Flexible Cord
- Custom print available upon request.

APPLICATIONS

- Vacuum Cleaner Cord, Food processors or Office Equipment

CONSTRUCTION

Bare copper conductor insulated with 105C PVC, twisted with or without fillers, and jacketed with 105C PVC to conform to UL and CSA. Rated for 300V. *18/2 and 18/3 fillerless enhanced with a micro poly strength member for mechanical strength.

| GAUGE | STRANDING | INSULATION THICKNESS | | JACKET THICKNESS | | NOMINAL O.D. WITH FILLER | | NOMINAL O.D. FILLERLESS | | STANDARD PACKAGE | SHIPPING WEIGHT -LBS/ 1000 FT. WITH FILLER | SHIPPING WEIGHT -LBS/ 1000 FT. FILLERLESS |
|-------|-----------|----------------------|------|------------------|------|--------------------------|------|-------------------------|------|------------------|--|---|
| | | in | mm | in | mm | in | mm | in | mm | | | |
| 18/2* | 41/.0063" | 0.015 | 0.38 | 0.030 | 0.76 | 0.245 | 6.22 | 0.245 | 6.22 | 15000 | 100 | 104 |
| 18/3* | 41/.0063" | 0.015 | 0.38 | 0.030 | 0.76 | 0.242 | 6.15 | 0.239 | 6.07 | 12000 | 72 | 86 |
| 16/2 | 65/.0063" | 0.015 | 0.38 | 0.030 | 0.76 | 0.250 | 6.35 | N/A | N/A | 10000 | 87 | N/A |
| 16/3 | 65/.0063" | 0.015 | 0.38 | 0.030 | 0.76 | 0.269 | 6.83 | 0.266 | 6.76 | 10000 | 120 | 120 |

Specifications contained herein reflect current data and are subject to change. Values are nominal and/or approximate.

* This product can be designed to meet customer specification

ISO 9001:2015 CERTIFIED
ISO 14001:2015 CERTIFIED

KALAS MAILING ADDRESS
167 Greenfield Road
Lancaster, PA 17601

TULSA WAREHOUSE
1810 East Jasper St.
Tulsa, Oklahoma 74110

KALASWIRE.COM
P 717-336-5575

MADE IN USA