

SPEAKER WIRE



FEATURES

- Insulation contains UV protection against yellowing.
- Special stranding and packaging available upon request.
- Custom print available upon request.

APPLICATIONS

- For connection of speakers to an A/V receiver or amplifier

CONSTRUCTION

Stranded flexible copper conductor insulated with clear 105°C PVC to form a two conductor parallel speaker wire.

GAUGE	STRANDING	INSULATION THICKNESS		MINOR		MAJOR		STANDARD PACKAGE	SHIPPING WEIGHT -LBS/ 1000 FT.
		in	mm	in	mm	in	mm		
18/2	16/010 Bare 16/010 Tinned	0.023	0.58	0.094	2.39	0.194	4.93	5000	17

Specifications contained herein reflect current data and are subject to change. Values are nominal and/or approximate.

KALAS HEADQUARTERS
167 Greenfield Road
Lancaster, PA 17601

KALAS LOS ANGELES
28365 Constellation Road,
Unit B
Valencia, CA 91355

KALASWIRE.COM
P 717.336.5575
F 717.945.1002



ISO 9001:2015 CERTIFIED
ISO 14001:2015 CERTIFIED

RoHS: Kalas products are compliant with the requirements of the RoHS directive (2011/65/EU as amended).

MADE IN THE USA