

TRACER WIRE



FEATURES

- Temperature rating is -65°C to 75°C with 30 Volts or 600 Volts
- Available with UL labeling and print
- Direct burial
- Custom print available upon request
- Sunlight resistant
- Other stranding available upon request

CONSTRUCTION

Solid conductor insulated with high grade polyethylene to form a durable single conductor Tracer wire with bare copper.

APPLICATIONS

- Single conductor constructions for use in direct burial applications where you may need to locate piping using the wire.

TRACER WIRE



SOLID BARE COPPER TRACER WIRE INSULATED WITH LINEAR LOW DENSITY POLYETHYLENE

GAUGE	STRANDING	INSULATION THICKNESS		Nominal O.D.		STANDARD PACKAGE	SHIPPING WEIGHT -LBS/ 1000 FT.
		in	mm	in	mm		
14	SBC 1/.0641"	0.030"	7.62	0.127"	32.26	1000	16
14	SBC 1/.0641"	0.045"	11.43	0.157"	39.88	1000	19
12	SBC 1/.0808"	0.030"	7.62	0.144"	36.58	1000	25
12	SBC 1/.0808"	0.045"	11.43	0.174"	44.20	1000	28
10	SBC 1/.1019"	0.030"	7.62	0.165"	41.91	1000	37
10	SBC 1/.1019"	0.045"	11.43	0.195"	49.53	1000	40

Please contact your Kalas representative to discuss ampacity and voltage drop values based on NEC standards.

KALAS MAILING ADDRESS
167 Greenfield Road
Lancaster, PA 17601

KALASWIRE.COM
P 717-335-0135

LAS VEGAS WAREHOUSE
4320 North Lamb Blvd.
Suite 300,
Las Vegas, Nevada 89115

TULSA WAREHOUSE
1810 East Jasper St.
Tulsa, Oklahoma 74110