

TRACER WIRE



FEATURES

- Temperature rating is -65°C to 75°C with 30 Volts or 600 Volts
- Available with UL labeling and print
- Direct burial
- Custom print available upon request
- Sunlight resistant
- Other stranding available upon request

APPLICATIONS

- Single conductor constructions for use in direct burial applications where you may need to locate piping using the wire.

CONSTRUCTION

Solid bare copper conductor insulated with Linear Low Density Polyethylene to form a durable tracer wire.

TRACER WIRE



SOLID BARE COPPER TRACER WIRE INSULATED WITH LINEAR LOW DENSITY POLYETHYLENE

GAUGE	STRANDING	INSULATION THICKNESS		Nominal O.D.		STANDARD PACKAGE	SHIPPING WEIGHT -LBS/ 1000 FT.
		in	mm	in	mm		
14	SBC 1/.0641"	0.030"	7.62	0.127"	32.26	1000	16
14	SBC 1/.0641"	0.045"	11.43	0.157"	39.88	1000	19
12	SBC 1/.0808"	0.030"	7.62	0.144"	36.58	1000	25
12	SBC 1/.0808"	0.045"	11.43	0.174"	44.20	1000	28
10	SBC 1/.1019"	0.030"	7.62	0.165"	41.91	1000	37
10	SBC 1/.1019"	0.045"	11.43	0.195"	49.53	1000	40

KALAS MAILING ADDRESS
 167 Greenfield Road
 Lancaster, PA 17601

TULSA WAREHOUSE
 1810 East Jasper St.
 Tulsa, Oklahoma 74110

KALASWIRE.COM
 P 717-336-5575