

AUTOMOTIVE DUPLEX



FEATURES

- Special stranding and packaging are available upon request.
- Custom print available upon request.

Applications

- Trucks, Buses, Trailers and General Use.

CONSTRUCTION

Stranded copper conductor insulated with PVC (GPT 80° or 105°C) and jacketed with 80° C or 105°C PVC to form a flat multiconductor cable. Operating temperatures -40°C min to 80°C or 105°C max. Inner conductors meet SAE J1128 with a 60VDC voltage rating per the standard.

AUTOMOTIVE DUPLEX



GAUGE	STRANDING	INSULATION THICKNESS		JACKET THICKNESS		MINOR		MAJOR		STANDARD PACKAGING	SHIPPING WEIGHT LBS/1000 FT
		IN	MM	IN	MM	IN	MM	IN	MM		
18/2	16/010	0.023	0.58	0.028	0.71	0.150	3.81	0.244	6.20	3500	26
16/2	19/0112	0.023	0.58	0.028	0.71	0.160	4.06	0.262	6.65	5000	33
14/2	19/0140	0.023	0.58	0.030	0.76	0.182	4.62	0.280	7.11	8000	46
12/2	19/0177	0.026	0.66	0.030	0.76	0.208	5.28	0.350	8.89	6000	64
10/2	19/0223	0.031	0.79	0.030	0.76	0.235	5.97	0.410	10.41	4000	96

KALAS MAILING ADDRESS
 167 Greenfield Road
 Lancaster, PA 17601

TULSA WAREHOUSE
 1810 East Jasper St.
 Tulsa, Oklahoma 74110

KALASWIRE.COM
 P 717-336-5575