

AUTOMOTIVE QUADRUPLIX



FEATURES

- Special stranding and packaging are available upon request.
- Custom print available upon request.

Applications

- Trucks, Buses, Trailers and General Use.

CONSTRUCTION

Stranded copper conductor insulated with PVC (GPT 80° or 105°C) and jacketed with 80° C or 105°C PVC to form a flat multiconductor cable. Operating temperatures -40°C min to 80°C or 105°C max. Inner conductors meet SAE J1128 with a 60VDC voltage rating per the standard.

AUTOMOTIVE QUADRUPLEX



GAUGE	STRANDING	INSULATION THICKNESS		JACKET THICKNESS		MAJOR O.D.		MINOR O.D.		STANDARD PACKAGING	SHIPPING WEIGHT LBS/1000 FT
		IN	MM	IN	MM	IN	MM	IN	MM		
16/4	19/0112	0.023	0.58	0.024	0.61	0.160	4.06	0.468	11.89	5000	61
14/4	19/0140	0.023	0.58	0.024	0.61	0.165	4.19	0.524	13.31	4000	83
12/4	19/0177	0.026	0.66	0.030	0.76	0.208	5.28	0.634	16.10	1000	125

KALAS MAILING ADDRESS
167 Greenfield Road
Lancaster, PA 17601

TULSA WAREHOUSE
1810 East Jasper St.
Tulsa, Oklahoma 74110

KALASWIRE.COM
P 717-336-5575