

AUTOMOTIVE TRIPLEX



FEATURES

- Special stranding and packaging are available upon request.
- Custom print available upon request.

Applications

- Trucks, Buses, Trailers and General Use.

CONSTRUCTION

Stranded copper conductor insulated with PVC (GPT 80° or 105°C) or XLPE (GXL 125°C) and jacketed with 80° C or 105°C PVC to form a flat multiconductor cable. Operating temperatures -40°C min to 80°C or 105°C max. Inner conductors meet SAE J1128.

AUTOMOTIVE TRIPLEX



GAUGE	STRANDING	INSULATION THICKNESS		JACKET THICKNESS		MINOR		MAJOR		STANDARD PACKAGING	SHIPPING WEIGHT LBS/1000 FT
		IN	MM	IN	MM	IN	MM	IN	MM		
16/3	19/0112	0.023	0.58	0.028	0.71	0.160	4.06	0.365	9.27	7000	46
14/3	19/0140	0.023	0.58	0.030	0.76	0.177	4.50	0.415	10.54	6000	64
12/3	19/0177	0.026	0.66	0.030	0.76	0.208	5.28	0.486	12.34	4000	94

Please contact your Kalas representative to discuss ampacity and voltage drop values based on NEC standards.

KALAS MAILING ADDRESS
167 Greenfield Road
Lancaster, PA 17601

KALASWIRE.COM
P 717-335-0135

LAS VEGAS WAREHOUSE
4320 North Lamb Blvd.
Suite 300,
Las Vegas, Nevada 89115

TULSA WAREHOUSE
1810 East Jasper St.
Tulsa, Oklahoma 74110