

# AUTOMOTIVE TRIPLEX



## FEATURES

- Special stranding and packaging are available upon request.
- Custom print available upon request.

## Applications

- Trucks, Buses, Trailers and General Use.

## CONSTRUCTION

Stranded copper conductor insulated with PVC (GPT 80 or 105°C) and jacketed with 80 or 105°C PVC jacket to form a flat multiconductor cable. Operating temperatures -40°C min to 80°C or 105°C max. Inner conductors meet SAE J1128 with a 60VDC voltage rating per the standard.

# AUTOMOTIVE TRIPLEX



GAUGE	STRANDING	INSULATION THICKNESS		JACKET THICKNESS		MINOR		MAJOR		STANDARD PACKAGING	SHIPPING WEIGHT LBS/1000 FT
		IN	MM	IN	MM	IN	MM	IN	MM		
18/3	16/0100	0.023	0.5842	0.028	0.7112	0.153	3.8862	0.334	8.4836	1500	40
16/3	19/0112	0.023	0.58	0.028	0.71	0.160	4.06	0.365	9.27	7000	46
14/3	19/0140	0.023	0.58	0.030	0.76	0.177	4.50	0.415	10.54	6000	64
12/3	19/0177	0.026	0.66	0.030	0.76	0.208	5.28	0.486	12.34	4000	94
10/3	19/0223	0.031	0.7874	0.030	0.762	0.242	6.1468	0.59	14.986	1500	150

**KALAS MAILING ADDRESS**  
 167 Greenfield Road  
 Lancaster, PA 17601

**TULSA WAREHOUSE**  
 1810 East Jasper St.  
 Tulsa, Oklahoma 74110

**KALASWIRE.COM**  
 P 717-336-5575