

# CLEAR GROUNDING CABLE



## FEATURES

- Superior flexibility ensures ultimate ease of use.
- Clear PVC jacket ensures ability to see copper stranding and identify breaks.
- Jacket meets the operating temperature range and flame retardancy of ASTM F-855 Type III.
- Heavier jacket walls provide extra protection for copper conductor.
- Excellent cold weather properties to -40°C exceeding ASTM F-855.
- Superior maximum operating temperature range up to 105°C exceeding ASTM F-855 Type III.
- Special and packaging are available upon request.
- Standard indent print with custom inkjet print available upon request.



## APPLICATIONS

- Temporary grounding for de-energized overhead electrical lines and de-energized electrical equipment.

## CONSTRUCTION

Highly flexible stranded No. 30 bare copper conductor insulated with a high grade RoHS compliant 105°C clear PVC jacket.

# CLEAR GROUNDING CABLE



GAUGE	STRANDING	INSULATION THICKNESS		NOMINAL O.D.		STANDARD PACKAGE	SHIPPING WEIGHT -LBS/ 1000 FT.
		in	mm	in	mm		
2	7/95/.010	0.110	2.79	0.530	13.46	500 or 1000	287
1/0	19/56/.010	0.127	3.23	0.650	16.51	500 or 1000	445
2/0	19/70/.010	0.127	3.23	0.700	17.78	500 or 1000	545
3/0	19/88/010	0.142	3.61	0.784	19.91	500 or 1000	684
4/0	19/111/.010	0.142	3.61	0.850	21.59	500 or 1000	839

Please contact your Kalas representative to discuss ampacity and voltage drop values based on NEC standards.

**KALAS MAILING ADDRESS**  
167 Greenfield Road  
Lancaster, PA 17601

**KALASWIRE.COM**  
P 717-336-5575

**LAS VEGAS WAREHOUSE**  
4320 North Lamb Blvd.  
Suite 300,  
Las Vegas, Nevada 89115

**TULSA WAREHOUSE**  
1810 East Jasper St.  
Tulsa, Oklahoma 74110