

BOOSTER DUPLEX



FEATURES

- Alternative copper, insulations, and packaging are available upon request
- Custom constructions also available with pilot wire

APPLICATIONS

- Cable used as temporary starter for battery-powered vehicles.

CONSTRUCTION

Highly flexible stranded copper extruded with a high grade TPE or PVC. Operating temperatures are available from 105°C to temperatures as low as -60°C. One leg ribbed or colored for easy identification of polarity.

BOOSTER DUPLEX



GAUGE	STRANDING	INSULATION THICKNESS		NOMINAL O.D.		STANDARD PACKAGE	SHIPPING WEIGHT -LBS/ 1000 FT.
		in	mm	min. x maj. in	min. x maj. mm		
10/2	104/.010"	0.030"	7.62	0.180" x 0.375"	45.72 x 95.25	1500	80
8/2	7/24/.010"	0.060"	15.24	0.285" x 0.575"	72.39 x 146.05	1000	145
6/2	7/36/.010"	0.090"	22.86	0.380" x 0.845"	96.52 x 214.63	500	258
4/2	7/52/.010"	0.077"	19.55	0.400" x 0.930"	101.6 x 120.65	500	338
2/2	12/52/.010"	0.087"	22.10	0.475" x 1.075"	137.16 x 273.05	1000	553
1/2	12/65/.010"	0.100"	25.4	0.540" x 1.230"	137.16 x 312.42	1250	673
1/0 - 2	19/52/.010"	0.080"	20.32	0.550" x 1.210"	139.70 x 307.34	2000	755

KALAS MAILING ADDRESS
 167 Greenfield Road
 Lancaster, PA 17601

TULSA WAREHOUSE
 1810 East Jasper St.
 Tulsa, Oklahoma 74110

KALASWIRE.COM
 P 717-336-5575