



FEATURES

- Special stranding and packaging are available upon request.
- Resistant to acid, abrasion, alkalis, coolant, diesel fuel, ethanol, flame, gas, ozone, power steering fluid, oil and transmission fluid.
- Custom print available upon request.

APPLICATIONS

- For use in boats, buses, cars, lift trucks, RV's, tractors and trucks.

CONSTRUCTION

SAE GPT Primary Wire 60V DC is constructed with flexible stranded copper conductor. Insulation is a high grade 80°C PVC, also available in 105°C PVC.

Kalas GPT Primary Wire is constructed to meet the requirements of SAE J1128. TWP is available upon request.

PRIMARY WIRE GPT



GAUGE	STRANDING	INSULATION THICKNESS		NOMINAL O.D.		STANDARD PACKAGE REEL OR DRUM	SHIPPING WEIGHT -LBS/ 1000 FT.
		in	mm	in	mm		
18	16/.010	0.023	0.58	0.094	2.39	6000 / 50000	8.5
16	19/.0112	0.023	0.58	0.103	2.62	5000 / 30000	11
14	19/.0140	0.023	0.58	0.117	2.97	4000 / 25000	16
12	19/.0177	0.026	0.66	0.142	3.61	2500 / 18000	25
10	19/.0223	0.031	0.79	0.168	4.27	1500 / 12000	39
8	19/.0281	0.037	0.94	0.208	5.28	1000 / 8000	60

KALAS MAILING ADDRESS
167 Greenfield Road
Lancaster, PA 17601

KALASWIRE.COM
P 717-336-5575

TULSA WAREHOUSE
1810 East Jasper St.
Tulsa, Oklahoma 74110