

# TPE GROUNDING CABLE



## FEATURES

- Excellent operating temperature range from -40°C to 105°C, surpasses requirements of ASTM F-855.
- Superior flexibility in cold weather.
- Indent and ink jet print available.
- Custom print available upon request.
- Special packaging available upon request.

## APPLICATIONS

- Temporary grounding for de-energized overhead electrical lines and de-energized electrical equipment.

## CONSTRUCTION

Highly flexible stranded No. 30 bare copper conductor insulated with a high grade RoHS compliant 105°C TPE jacket.

# TPE GROUNDING CABLE



GAUGE	STRANDING	INSULATION THICKNESS		NOMINAL O.D.		STANDARD PACKAGE	SHIPPING WEIGHT -LBS/ 1000 FT.
		in	mm	in	mm		
2	7/95/.010	0.090	2.29	0.493	12.52	500 or 1000	271
1/0	19/56/.010	0.090	2.29	0.576	14.63	500 or 1000	394
2/0	19/70/.010	0.100	2.54	0.646	16.41	500 or 1000	516
3/0	19/88/.010	0.100	2.54	0.700	17.78	500 or 1000	648
4/0	19/111/.010	0.100	2.54	0.770	19.56	500 or 1000	784

Please contact your Kalas representative to discuss ampacity and voltage drop values based on NEC standards.

**KALAS MAILING ADDRESS**  
167 Greenfield Road  
Lancaster, PA 17601

**KALASWIRE.COM**  
P 717-336-5575

**LAS VEGAS WAREHOUSE**  
4320 North Lamb Blvd.  
Suite 300,  
Las Vegas, Nevada 89115

**TULSA WAREHOUSE**  
1810 East Jasper St.  
Tulsa, Oklahoma 74110