

LOW ENERGY CIRCUIT CABLE / LANDSCAPE LIGHTING UL-ULECC, c(UL) ULEC



FEATURES

- Special stranding and packaging available upon request
- Custom print available upon request
- Direct Burial
- Sunlight Resistant
- Sequential print available

CONSTRUCTION

Stranded bare copper conductor insulated with high grade PVC to form a 2 conductor parallel landscape lighting cable. One leg has raised ridges to easily identify polarity. UL and c(UL) listed. Operating temperature range is 60°C to -25°C. Voltage rating is 30V.

APPLICATIONS

- Landscape Lighting

LOW ENERGY CIRCUIT CABLE / LANDSCAPE LIGHTING



GAUGE	STRANDING	INSULATION THICKNESS		MINOR		MAJOR		STANDARD PACKAGE	SHIPPING WEIGHT -LBS/ 1000 FT.
		INCHES	MM	INCHES	MM	INCHES	MM		
18/2	16/010	0.045	1.1	0.290	7.4	0.145	3.7	500	28
16/2	26/010	0.045	1.1	0.320	8.1	0.160	4.1	500	36
14/2	41/010	0.045	1.1	0.350	8.9	0.175	4.4	500	49
12/2	65/010	0.045	1.1	0.390	9.9	0.195	5.0	500	68
10/2	104/010	0.045	1.1	0.440	11.2	0.220	5.6	500	95
8/2	168/010	0.060	1.5	0.575	14.6	0.285	7.2	500	158

KALAS MAILING ADDRESS
167 Greenfield Road
Lancaster, PA 17601

TULSA WAREHOUSE
1810 East Jasper St.
Tulsa, Oklahoma 74110

KALASWIRE.COM
P 717-336-5575