

LOW VOLTAGE LANDSCAPE LIGHTING



FEATURES

- Special stranding and packaging available upon request
- Custom print available upon request
- Direct Burial
- Sunlight Resistant
- Sequential print available

CONSTRUCTION

Stranded bare copper conductor insulated with high grade PVC to form a 2 conductor parallel landscape lighting cable. One leg has raised ridges to easily identify polarity. UL and c(UL) listed. Operating temperature range is 60°C to -25°C. Voltage rating is 30V.

APPLICATIONS

- Landscape Lighting

LOW VOLTAGE LANDSCAPE LIGHTING



GAUGE	STRANDING	INSULATION THICKNESS		MINOR		MAJOR		STANDARD PACKAGE	SHIPPING WEIGHT -LBS/ 1000 FT.
		INCHES	MM	INCHES	MM	INCHES	MM		
18/2	16/010	0.045	1.1	0.290	7.4	0.145	3.7	500	28
16/2	26/010	0.045	1.1	0.320	8.1	0.160	4.1	500	36
14/2	41/010	0.045	1.1	0.350	8.9	0.175	4.4	500	49
12/2	65/010	0.045	1.1	0.390	9.9	0.195	5.0	500	68
10/2	104/010	0.045	1.1	0.440	11.2	0.220	5.6	500	95
8/2	168/010	0.060	1.5	0.575	14.6	0.285	7.2	500	158

Please contact your Kalas representative to discuss ampacity and voltage drop values based on NEC standards.

KALAS MAILING ADDRESS
167 Greenfield Road
Lancaster, PA 17601

KALASWIRE.COM
P 717-336-5575

LAS VEGAS WAREHOUSE
4320 North Lamb Blvd.
Suite 300,
Las Vegas, Nevada 89115

TULSA WAREHOUSE
1810 East Jasper St.
Tulsa, Oklahoma 74110