

HD JACKETED SUBMERSIBLE PUMP CABLE



FEATURES

- Operating temperature range -40° C to 75° C
- Resistant to acid, abrasion, alkalis, flame, gas, and oil
- Water and sunlight resistant
- Cable is sequentially marked
- Special packaging is available upon request

APPLICATIONS

- For wiring within the casing of deep well submersible water pumps

CONSTRUCTION

Annealed bare stranded copper conductors PVC insulated and run parallel with a PVC black jacket to form a 75°C 600 Volt Multi-Conductor Submersible Pump Cable. UL Listed per UL 83 Type THW as Deep Well Submersible Pump Cable.

HD JACKETED SUBMERSIBLE PUMP CABLE



GAUGE	STRANDING	INSULATION THICKNESS		JACKET THICKNESS		NOMINAL O.D.		STANDARD PACKAGE	SHIPPING WEIGHT -LBS/1000 FT.	PART NUMBER
		in	mm	in	mm	min. x maj. in	min. x maj. mm			
14/2 with GND	19/.0147"	0.045	1.143	0.045	1.143	0.262 x 0.594	6.655 x 15.088	500 or 1000	110	440411.XX.001
14/3 with GND	19/.0147"	0.045	1.143	0.045	1.143	0.262 x 0.762	6.655 x 19.355	500 or 1000	136	440211.XX.001
12/2 with GND	19/.0185"	0.045	1.143	0.045	1.143	0.271 x 0.680	6.883 x 17.272	500 or 1000	143	440412.XX.001
12/3 with GND	19/.0185"	0.045	1.143	0.045	1.143	0.275 x 0.840	6.985 x 21.336	500 or 1000	187	440212.XX.001
10/2 with GND	19/.0234"	0.045	1.143	0.045	1.143	0.314 x 0.754	7.976 x 19.152	500 or 1000	200	440413.XX.001
10/3 with GND	19/.0234"	0.045	1.143	0.045	1.143	0.314 x 0.988	7.976 x 25.095	500 or 1000	267	440213.XX.001
8/3 with #10 GND	19/.0295" (#8 ga) – 19/.0234" (#10 ga)	0.060	1.524	0.050	1.27	0.375 x 1.135	9.525 x 28.829	500 or 1000	394	440214.XX.001
6/3 with #8 GND	19/.0372" (#6 ga) – 19/.0295" (#8 ga)	0.060	1.524	0.050	1.27	0.410 x 1.320	10.414 x 33.528	500 or 1000	560	440215.XX.001
4/3 with #8 GND	19/.0469" (#4 ga) – 19/.0295" (#8 ga)	0.060	1.524	0.050	1.27	0.468 x 1.465	11.887 x 37.211	500 or 1000	744	440216.XX.001
2/3 with #6 GND	19/.0591" (#2 ga) – 19/.0372" (#6 ga)	0.060	1.651	0.065	1.27	0.564 x 1.731	14.326 x 43.967	500 or 1000	1072	440217.XX.001

KALAS MAILING ADDRESS
167 Greenfield Road
Lancaster, PA 17601

TULSA WAREHOUSE
1810 East Jasper St.
Tulsa, Oklahoma 74110

KALASWIRE.COM
P 717-336-5575