

# TWISTED PVC SUBMERSIBLE PUMP CABLE



## FEATURES

- Operating temperature range -40° C to 75° C
- Resistant to acid, abrasion, alkalis, flame, gas, and oil
- Water and sunlight resistant
- Special packaging is available upon request

## CONSTRUCTION

Annealed bare solid or stranded copper conductors insulated with PVC and twisted to form a 75°C 600 Volt Multi-Conductor Submersible Pump Cable. UL Listed per UL 83 Type THW as Deep Well Submersible Pump Cable.

## APPLICATIONS

- For wiring within the casing of deep well submersible water pumps

# TWISTED PVC SUBMERSIBLE PUMP CABLE



GAUGE	STRANDING	INSULATION THICKNESS		TWISTED NOMINAL O.D.		STANDARD PACKAGE	SHIPPING WEIGHT -LBS/1000 FT.	PART NUMBER
		in	mm	in	mm			
14/2 with GND	Solid/.0641"	0.045	1.143	0.339	8.611	500 or 1000	67	440011.XX.999
14/3 with GND	Solid/.0641"	0.045	1.143	0.380	9.652	500 or 1000	89	440012.XX.999
12/2 with GND	Solid/.0808"	0.045	1.143	0.369	9.373	500 or 1000	94	440013.XX.999
12/3 with GND	Solid/.0808"	0.045	1.143	0.414	10.516	500 or 1000	125	440014.XX.999
10/2 with GND	Solid/.1019"	0.045	1.143	0.421	10.693	500 or 1000	136	440015.XX.999
10/3 with GND	Solid/.1019"	0.045	1.143	0.472	11.989	500 or 1000	182	440016.XX.999
8/2 with #10 GND	19/.0295" – solid (.1019")	0.060	1.524	0.538	13.665	500 or 1000	197	440017.XX.999
8/3 with #10 GND	19/.0295" – solid (.1019")	0.060	1.524	0.608	15.443	500 or 1000	273	440018.XX.999
6/3 with #8 GND	19/.0372" – 19/.0295"	0.060	1.524	0.728	18.491	500 or 1000	413	440019.XX.999
4/3 with #8 GND	19/.0469" – 19/.0295"	0.060	1.524	0.819	20.803	500 or 1000	584	440020.XX.999

Please contact your Kalas representative to discuss ampacity and voltage drop values based on NEC standards.

**KALAS MAILING ADDRESS**  
167 Greenfield Road  
Lancaster, PA 17601

**TULSA WAREHOUSE**  
1810 East Jasper St.  
Tulsa, Oklahoma 74110

**KALASWIRE.COM**  
P 717-336-5575