

# SPRINKLER WIRE FOR MAXI CONTROL SYSTEM



## CONSTRUCTION

Solid tinned copper conductors insulated with water resistant PVC to form a UL UF single then jacketed with a linier low density polyethylene to form a durable multiconductor sprinkler system wire for Maxi Control Systems. Temperature rating is 75°C to -65°C 600 Volts.

## FEATURES

- Available with UL labeling and print.
- Direct burial
- Sunlight resistant.

GAUGE	STRANDING	INSULATION THICKNESS		JACKET THICKNESS		NOMINAL O.D.		STANDARD PACKAGE	SHIPPING WEIGHT -LBS/ 1000 FT.
		in	mm	in	mm	min. x maj. in	min. x maj. mm		
14/2	Solid/.0641	0.060"	15.24	0.045"	11.43	0.470" x 0.280"	119.38 x 71.12	1000	77
12/2	Solid/.0808	0.060"	15.24	0.045"	11.43	0.300" x 0.506"	76.20 x 128.52	1000	101

For ampacities and voltage drop please refer to the National Electric Code (NEC) or a professional Electrical Engineer for your specific application. Specifications contained herein reflect current data and are subject to change. Values are nominal and/or approximate.

\* This product can be designed to meet customer specification

SPKLMX/3.20

### KALAS MAILING ADDRESS

167 Greenfield Road  
Lancaster, PA 17601

### KALASWIRE.COM

P 717-335-0135

**RoHS:** Kalas products are compliant with the requirements of the RoHS directive (2011/65/EU as amended).

### LAS VEGAS WAREHOUSE

4320 North Lamb Blvd.  
Suite 300,  
Las Vegas, Nevada 89115

### TULSA WAREHOUSE

1810 East Jasper St.  
Tulsa, Oklahoma 74110



MADE IN USA

ISO 9001:2015 CERTIFIED  
ISO 14001:2015 CERTIFIED