

# TWISTED PET CONTAINMENT WIRE



## FEATURES

- Special stranding, colors and packaging are available upon request
- Direct burial
- Sunlight resistant
- Available with UL labeling and print

## CONSTRUCTION

Solid or stranded copper conductor insulated with linear low density polyethylene to form a durable single or twisted fence wire for pet containment systems. Temperature rating is 75°C to -65°C 30 Volts or 600 Volts.

## TWISTED PET CONTAINMENT

GAUGE	STRANDING	INSULATION THICKNESS		NOMINAL O.D.		STANDARD PACKAGE	SHIPPING WEIGHT -LBS/ 1000 FT.
		in	mm	in	mm		
14/2	19/.0140	0.025"	6.35	0.240	60.96	500	30
16/2	19/.0112	0.025"	6.35	0.218	55.37	500	22

### KALAS MAILING ADDRESS

167 Greenfield Road  
Lancaster, PA 17601

### KALASWIRE.COM

P 717-335-0135

### LAS VEGAS WAREHOUSE

4320 North Lamb Blvd.  
Suite 300,  
Las Vegas, Nevada 89115

### TULSA WAREHOUSE

1810 East Jasper St.  
Tulsa, Oklahoma 74110

ISO 9001:2015 CERTIFIED  
ISO 14001:2015 CERTIFIED

Please contact your Kalas representative to discuss ampacity and voltage drop values based on NEC standards.

For ampacities and voltage drop please refer to the National Electric Code (NEC) or a professional Electrical Engineer for your specific application. Specifications contained herein reflect current data and are subject to change. Values are nominal and/or approximate.  
\* This product can be designed to meet customer specification

**RoHS:** Kalas products are compliant with the requirements of the RoHS directive (2011/65/EU as amended).



MADE IN USA