



GROUND



LEAD



STINGER / WHIP

- **Available Pre-Assembled with Leads, Grounds, and Stingers/Whips.** Available with all highly flexible welding cable products
- **Lenco® and Tweco® connectors** stocked and readily available
- **Durable Jacket**
Resists cuts, tears, abrasion, grease, oil, water, and flame
- **Colors**
Black, Blue, Green, Red, and Yellow jacket colors available.
- **Lengths**
Come in standard 25', 50' and 100' lengths.
Custom lengths available.
- **Packaging Options**
Coiled, boxed and shrink-wrapped packaging available

Pre-assembled lead, grounds and stinger/whips are ready-to-use, saving you time and reducing labor hours.

STOCK ASSEMBLIES TWECO	ITEM #	DESCRIPTION
1/0	10T1050B3334	1/0 BLK, 50' LGTH, 2MPC MALE/FEMALE
1/0	10T1100B3334	1/0 BLK,100' LGTH, 2MPC MALE/FEMALE
2/0	20T1025B3334	2/0 BLK, 25' LGTH, 2MPC MALE/FEMALE
2/0	20T1050B3334	2/0 BLK, 50' LGTH, 2MPC MALE/FEMALE
2/0	20T1100B3536	2/0 BLK, 100' LGTH, 2MPC MALE/FEMALE
Stock Assemblies Lenco	Item #	Description
1/0	10T1050B0809	1/0 BLK, 50' LGTH, LC-40 MALE/FEMALE
1/0	10T1100B0809	1/0 BLK,100' LGTH, LC-40 MALE/FEMALE
2/0	20T1050B0809	2/0 BLK, 50' LGTH, LC-40 MALE/FEMALE
2/0	20T1100B0809	2/0 BLK, 100' LGTH, LC-40 MALE/FEMALE

WELDING CABLE AMPACITY GUIDE:

GAUGE	50'	75'	100'	125'	150'	175'	200'	225'	250'	300'	350'
#6	100	100									
#4	150										
#2	200	150	100	100							
#1	250/300	200	150		100						
1/0	350	250	200	150		100	100				
2/0	400/450	300	250	200	150		100	100			
3/0	500	350/400	300	250	200	150	150			100	
4/0	550/600	450/500	350/400	300	250	200	200	150	150		100

KALAS MAILING ADDRESS
167 Greenfield Road
Lancaster, PA 17601

TULSA WAREHOUSE
1810 East Jasper St.
Tulsa, Oklahoma 74110

KALASWIRE.COM/INDUSTRIAL
P 717-335-0135

NOTE: Do not use for 600 volt in-line applications. Product for welding applications only. Specifications contained herein reflect current data and are subject to change. Values are nominal and/or approximate.

MADE IN USA
ISO 9001: 2015 CERTIFIED
ISO 14001: 2015 CERTIFIED

RoHS: Kalas products are compliant with the requirements of the RoHS directive (2011/65/EU as amended).