



- **Highly Flexible**
Bare stranded copper conductor insulated with PVC and jacketed with TPE conforming to UL and CSA.
- **Durable Jacket**
Resistant to oil, ozone, weather, sunlight and water
- **Operating Temperatures**
Range from -40°C to + 90°C (-40°F to + 194°F)
- **Rated to 600 Volts**
- **National Electrical Code article 400**
- **Stock Lengths**
250 ft. reels
- **Custom Lengths**
Available upon request
- **Sizes**
10/3, 10/4, 8/3, 8/4, 6/3, 6/4
- **UL 62 Flexible Cord;**
CSA Standard 22.2 No. 49

SPECIFICATIONS:

PART NUMBER	GAUGE	STRANDING	INSULATION THICKNESS		JACKET THICKNESS		NOMINAL O.D.		SHIPPING WEIGHT LBS./ 1000 FT.
			IN	MM	IN	MM	IN	MM	
530036.01.001	10/3	104/.010	0.045	1.14	0.095	2.41	0.655	16.64	242
530037.01.001	10/4	104/.010	0.045	1.14	0.095	2.41	0.729	18.52	299
530032.01.001	8/3	133/.0112	0.060	1.52	0.110	2.79	0.844	21.44	403
530033.01.001	8/4	133/.0112	0.060	1.52	0.125	3.18	0.975	24.77	510
530030.01.001	6/3	266/.010	0.060	1.52	0.125	3.18	0.969	24.61	548
530031.01.001	6/4	266/.010	0.060	1.52	0.140	3.56	1.081	27.46	721

Heavy Duty Flexible Cord for indoor use typically industrial machinery, appliances, heavy-duty tools, motors, and temporary indoor electrical power and lighting.

KALAS HEADQUARTERS
167 Greenfield Road
Lancaster, PA 17601

KALAS LOS ANGELES
28365 Constellation Road,
Unit B
Valencia, CA 91355

KALASWIRE.COM/INDUSTRIAL
P 717-335-0108
F 717 335-0846

Call 888 870-1997 for additional cable specifications.

Specifications contained herein reflect current data and are subject to change. Values are nominal and/or approximate.

ISO 9001: 2015 CERTIFIED
ISO 14001: 2015 CERTIFIED
MADE IN USA

