



- Highly Flexible**
 Bare stranded copper conductor insulated with EDPM and jacketed with EDPM conforming to UL and CSA.
- Durable Jacket**
 Resistant to oil, ozone, weather, sunlight and water
- Operating Temperatures**
 Range from -40°C to + 90°C (-40°F to + 194°F)
- Rated to 600 Volts**
- National Electrical Code article 400**
- Stock Lengths**
 250 ft. reels
- Custom Lengths**
 Available upon request
- Sizes**
 10/3, 10/4, 8/3, 8/4, 6/3, 6/4
- UL 62 Flexible Cord; CSA Standard 22.2 No. 49; MSHA Approved; RoHS Compliant

SPECIFICATIONS:

PART NUMBER	GAUGE	STRANDING	INSULATION THICKNESS		NOMINAL O.D.		CURRENT AMPS	SHIPPING WEIGHT LBS./ 1000 FT.
			IN	MM	IN	MM		
530154.01.001	8/3	133/29	0.06	1.52	0.84	21.34	40	242
530155.01.001	8/4	133/29	0.06	1.52	0.945	24	35	299
530157.01.001	6/4	133/27	0.06	1.52	1.08	27.43	45	403
530156.01.001	6/3	133/27	0.06	1.52	0.98	24.89	55	510
530153.01.001	10/4	104/30	0.045	1.14	0.715	18.16	25	548
530152.01.001	10/3	104/30	0.045	1.14	0.66	16.76	30	721

Heavy Duty Flexible Cord for indoor and outdoor use including industrial machinery appliances, heavy-duty tools, motors, and temporary indoor and outdoor electrical power and lighting.

KALAS MAILING ADDRESS
 167 Greenfield Road
 Lancaster, PA 17601

TULSA WAREHOUSE
 1810 East Jasper St.
 Tulsa, Oklahoma 74110

KALASWIRE.COM/INDUSTRIAL
 P 717-335-0135

NOTE: Do not use for 600 volt in-line applications. Product for welding applications only. Specifications contained herein reflect current data and are subject to change. Values are nominal and/or approximate.

MADE IN USA
 ISO 9001: 2015 CERTIFIED
 ISO 14001: 2015 CERTIFIED