



- **Highly Flexible**
Bare stranded copper conductor insulated with EDPM and jacketed with EDPM conforming to UL and CSA.
- **Durable Jacket**
Resistant to oil, ozone, weather, sunlight and water
- **Operating Temperatures**
Range from -40°C to + 90°C (-40°F to + 194°F)
- **Rated to 600 Volts**
- **National Electrical Code article 400**
- **Stock Lengths**
250 ft. reels
- **Custom Lengths**
Available upon request
- **Sizes**
10/3, 10/4, 8/3, 8/4, 6/3, 6/4
- **UL 62 Flexible Cord;**
CSA Standard 22.2 No. 49;
MSHA Approved;
RoHS Compliant

SPECIFICATIONS:

PART NUMBER	GAUGE	STRANDING	INSULATION THICKNESS		NOMINAL O.D.		CURRENT AMPS	SHIPPING WEIGHT LBS./ 1000 FT.
			IN	MM	IN	MM		
530154.01.001	8/3	133/29	0.06	1.52	0.84	21.34	40	242
530155.01.001	8/4	133/29	0.06	1.52	0.945	24	35	299
530157.01.001	6/4	133/27	0.06	1.52	1.08	27.43	45	403
530156.01.001	6/3	133/27	0.06	1.52	0.98	24.89	55	510
530153.01.001	10/4	104/30	0.045	1.14	0.715	18.16	25	548
530152.01.001	10/3	104/30	0.045	1.14	0.66	16.76	30	721

Heavy Duty Flexible Cord for indoor and outdoor use including industrial machinery appliances, heavy-duty tools, motors, and temporary indoor and outdoor electrical power and lighting.

KALAS MAILING ADDRESS
167 Greenfield Road
Lancaster, PA 17601

KALASWIRE.COM/INDUSTRIAL
P 717-335-0135

LAS VEGAS WAREHOUSE
4320 North Lamb Blvd.
Suite 300,
Las Vegas, Nevada 89115

TULSA WAREHOUSE
1810 East Jasper St.
Tulsa, Oklahoma 74110

NOTE: Do not use for 600 volt in-line applications. Product for welding applications only. Specifications contained herein reflect current data and are subject to change. Values are nominal and/or approximate.

RoHS: Kalas products are compliant with the requirements of the RoHS directive (2011/65/EU as amended).

MADE IN USA
ISO 9001: 2015 CERTIFIED
ISO 14001: 2015 CERTIFIED

