



- **Highly Flexible**
Annealed 30 gauge bare copper conductor, EPDM inner insulated with a high grade RoHS compliant CPE jacket
- **Superior Ease of Use**
Exceptional flexibility when coiling, transporting and storing cable
- **Highly Durable**
Resistant to abrasion, sunlight, chemical, oil and water
- **Operating Temperatures**
Range from -40°C to +90°C (-40°F to +194°F); Wet rating 90°C; 75°C oil resistant
- **Rated to 2000 Volts**
- **National Electrical Code article 400 and NFPA 70**
- **UL Subject 1650, CSA PPC 22.2 - 96**
- **MSHA Flame Test Approved**
- **PermaPrint™ Indent Printing**
Lifetime lasting indented print
- **Custom Print Legend**
Available in surface or indent print upon request
- **Standard Packaging**
#8 - 4/0 - 500 and 1,000' reels;
1/0 - 4/0 - 2,000' reels
- **Sizes**
#8 - 4/0

SPECIFICATIONS:

GAUGE	STRANDING	INSULATION THICKNESS		JACKET THICKNESS		NOMINAL O.D.		SHIPPING WEIGHT LBS/1000'
		IN	MM	IN	MM	IN	MM	
8	7x24/.0100"	0.060	1.52	0.075	1.91	0.445	11.30	132
6	7x38/.010"	0.060	1.52	0.095	2.41	0.525	13.32	195
4	7x60/.010"	0.060	1.52	0.095	2.41	0.592	15.02	264
2	7x95/.010"	0.060	1.52	0.095	2.41	0.645	16.37	352
1	19x44/.010"	0.080	2.03	0.095	2.41	0.725	18.40	454
1/0	19x56/.010"	0.080	2.03	0.095	2.41	0.775	19.67	535
2/0	19x70/.010"	0.080	2.03	0.095	2.41	0.828	21.02	643
3/0	19x88/.010"	0.080	2.03	0.095	2.41	0.883	22.42	782
4/0	19x111/.010"	0.080	2.03	0.095	2.41	0.953	24.19	941

Kalas Type W Cable offers superior flexibility for moving around objects & coiling for storage after temporary power requirements. Designed specifically for use in heavy duty & temporary power supply applications. Cable is also suitable for generator, motor, and battery leads as well as light to medium duty mining applications.

KALAS HEADQUARTERS
167 Greenfield Road
Lancaster, PA 17601

KALAS LOS ANGELES
28365 Constellation Road,
Unit B
Valencia, CA 91355

KALASWIRE.COM/INDUSTRIAL
P 717-335-0108
F 717 335-0846

Call 888 870-1997 for additional cable specifications.

Specifications contained herein reflect current data and are subject to change. Values are nominal and/or approximate.



ISO 9001: 2015 CERTIFIED
ISO 14001: 2015 CERTIFIED

MADE IN USA

